



DELL PowerEdge T160 server 2 TB Tower (3U) Intel® Xeon® 6325P 3.5 GHz 16 GB DDR5-SDRAM 300 W

Brand : DELL

Product family: PowerEdge

Product name : T160

DELL PowerEdge T160. Processor family: Intel® Xeon®, Processor frequency: 3.5 GHz, Processor model: 6325P. Internal memory: 16 GB, Internal memory type: DDR5-SDRAM. Total storage capacity: 2 TB, HDD size: 3.5", HDD interface: SATA III. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 300 W. Chassis type: Tower (3U)



Processor		Network	
Processor manufacturer *	Intel	Ethernet LAN	✓
Processor family *	Intel® Xeon®	Cabling technology	10/100/1000Base-T(X)
Processor model *	6325P	Ethernet interface type	Gigabit Ethernet
Processor frequency *	3.5 GHz	Ports & interfaces	
Processor boost frequency	5.2 GHz	Ethernet LAN (RJ-45) ports *	2
Performance cores	4	USB 2.0 ports quantity	3
Processor cores	4	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
Processor cache	12 MB	VGA (D-Sub) ports quantity	1
Number of processors installed	1	Serial ports quantity	1
Thermal Design Power (TDP)	55 W	Design	
System bus rate	16 GT/s	Chassis type *	Tower (3U)
Memory types supported by processor	DDR5-SDRAM	Product colour	Grey
Memory clock speeds supported by processor	4800 MHz	Performance	
Memory		Remote administration	iDRAC9, Basic 16G
Internal memory *	16 GB	Software	
Internal memory type *	DDR5-SDRAM	Operating system installed *	✗
Buffered memory type	Unregistered (unbuffered)	Compatible operating systems * Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi	
Memory slots	4x DIMM		
ECC	✓	Power	
Memory data transfer rate	5600 MT/s	Redundant power supply (RPS) support *	✗
Maximum internal memory *	128 GB	Power supply *	300 W
Storage			
Total storage capacity *	2 TB		
Number of HDDs installed	1		
HDD capacity	2 TB		
HDD interface	SATA III		

Storage		Operational conditions	
HDD speed	7200 RPM	Storage temperature (T-T)	-40 - 65 °C
HDD size	3.5"	Storage relative humidity (H-H)	5 - 95%
Number of HDDs supported	3	Operating altitude	0 - 3048 m
Supported HDD sizes	3.5"	Non-operating altitude	0 - 12000 m
Optical drive type *	×	Weight & dimensions	
Network		Width	132.5 mm
LAN controller	Broadcom 5720	Height	332.5 mm
Packaging content			
		Packaging content	Power Cord - C13, 3M, 125V, 15A
Other features			
		Bytes per sector	512n



0884116485827



884116485827

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.